

RACE

TRACK **MACH Heemstede**

NAME **John Ermen**

CITY / COUNTRY **St Willebrord / The Netherlands**

DATE **18-6-2017**

TEMPERATURE	AIR	TRACK		
QUALIFYING POSITION	BEST LAP TIME 13.73 SEC	FINAL POSITION	RACE LENGTH	
TRACK CONDITION		<input checked="" type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input type="checkbox"/> FAST
TRACTION		<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH

GEAR RATIO CHART

Spur	Spur 1st			Spur 2nd		
Pinion	60	61	62	56	57	58
1st 19T	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	5.37	5.46	5.56
2nd 24T	7.26	7.38	7.51	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Front SHOCK		Rear SHOCK	
OIL 500 CST	<input checked="" type="checkbox"/> 1 HOLE <input type="checkbox"/> 2 HOLE	SHOCK PISTON	<input type="checkbox"/> 1 HOLE <input checked="" type="checkbox"/> 2 HOLE
SPRING Red	HOLE SIZE 1.0 mm	SPRING Green	

Front TIRE		Rear TIRE	
Front Left 32 °	Tire Shore	Rear Left 35 °	Tire Ø
Front Right 32 °		Rear Right 35 °	
Front Left 69 mm	Tire Additive	Rear Left 76 mm	Tire Additive
Front Right 69 mm		Rear Right 76 mm	

BODY

Bumper <input checked="" type="checkbox"/> Standard <input type="checkbox"/> Cut	BODY MOUNT DISTANCE 10 mm
BODY TS040	WING 7 mm

ENGINE

Engine REDS WCS	Pipe 2095
Plug TS7	Carb Dia 9 mm
Fuel MLC	Head Shims 0.55 mm

CLUTCH

Clutch Bell Alu	Clutch Shoes Std.
Spring Load 0,6 mm	Bell Clearance 0.70 mm

NOTE

This setup was with R819005 in middle position. With part R802041 on lower arm.

FRONT BODY TOWER		DISK		CASTER	
Front <input checked="" type="checkbox"/>	Rear <input type="checkbox"/>	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	2 mm	
WHEEL BASE 0 mm		BUMP STEER 4 mm		REAR UPRIGHT SHIMS 0 mm	

FRONT		REAR	
RIDE HEIGHT 7.5 mm	FRONT UPPER ARM <input checked="" type="checkbox"/> Short <input type="checkbox"/> Medium <input type="checkbox"/> Long	<input checked="" type="checkbox"/> 1 HOLE <input type="checkbox"/> 2 HOLES INSIDE <input type="checkbox"/> 2 HOLES OUTSIDE	RIDE HEIGHT 9 mm
WHEEL SHIMS 0.5 mm	CAMBER 2.5/2 °	CAMBER 3/2.5 °	WHEEL SHIMS 1.5 mm
DOWN STOP 0 mm	+0mm <input type="checkbox"/> R801021 +2mm <input type="checkbox"/> R801022	REAR ROLL CENTER <input checked="" type="checkbox"/>	I-TYPE <input type="checkbox"/>
		REAR UPPER LINK <input checked="" type="checkbox"/>	DOWN STOP 9 mm

REAR TOE IN 2.0 °	FRONT TOE OUT 1.5 °
REAR ANTI-ROLL BAR 2.6 mm	FRONT ANTI-ROLL BAR 2.2 mm
UPPER DECK <input checked="" type="checkbox"/> FIX <input type="checkbox"/> FLEX	UPPER DECK <input checked="" type="checkbox"/> FIX <input type="checkbox"/> REMOVED
ACKERMAN <input checked="" type="checkbox"/>	SLIDE WEIGHT <input checked="" type="checkbox"/> REMOVED <input type="checkbox"/> 0 %
TRACK WIDTH 265 mm	TRACK WIDTH 254 mm